


P0450DAS-SOD123FL

Description

Thyristors are a type of semi-conduct component. They are designed to protect baseband equipment from damaging overvoltage transients. such as modems, telephones, line cards, answering machines, FAX machines, T1/E1, xDSL and more.



Features


- Excellent capability of absorbing transient surge
- Quick response to surge voltage (ns Level)
- Eliminates overvoltage caused by fast rising transients
- Moisture sensitivity level: Level 1
- Fails short circuit when surged in excess of ratings
- Non degenerative

Device Symbol



Typical Applications

| Parameter | Definition |
|-----------|--|
| V_{DRM} | Peak Off-state Voltage – maximum voltage that can be applied while maintaining off state |
| V_S | Switching Voltage – maximum voltage prior to switching to on state |
| V_T | On-state Voltage – maximum voltage measured at rated on-state current |
| I_{DRM} | Leakage Current – maximum peak off-state current measured at V_{DRM} |
| I_S | Switching Current – maximum current required to switch to on state |
| I_T | On-state Current – maximum rated continuous on-state current |
| I_H | Holding Current – minimum current required to maintain on state |
| C_O | Off-state Capacitance – typical capacitance measured in off state |
| I_{PP} | Peak Pulse Current – maximum rated peak impulse current |



Thermal Consideration

| Parameter | Symbol | Value | Unit |
|---|-----------|-------------|------|
| Operating Temperature | T_J | -40 to +125 | °C |
| Storage Temperature | T_{STG} | -40 to +125 | °C |
| Junction to free air thermal resistance | R_{QJA} | 90 | W/°C |

Summary Electrical Characteristics, $T_a = 25 \pm 3^\circ C$ (Unless Otherwise Noted)

| Parameter Description | I _{DRM} @V _{DRM} | | V _S ^① @I _S | | V _T @I _T | | I _H | C _O ^② |
|-----------------------|------------------------------------|----|---|-----|--------------------------------|-----|----------------|-----------------------------|
| Unit | μA | V | V | mA | V | A | mA | pF |
| Type | max | | max | max | max | max | Type | Type |
| P0450DA | 1 | 36 | 58 | 800 | 4 | 2.2 | 50 | 60 |





①Vs is measured at 100KV/s

②Off-state capacitance is measured in VDC=2V, VRMS=1V, f=1MHz


Surge Ratings

| Type | Wave Sharp | VPP |
|--------------|------------------|-------|
| IEC61000-4-5 | Voltage 10/700μs | 3000V |

Rating & Characteristic Curves



PACKAGE OUTLINE DIMENSIONS in millimeters



Disclaimer

Specifications are subject to change without notice.

The device characteristics and parameters in this data sheet can and do vary in different applications and actual device performance may vary over time.

Users should verify actual device performance in their specific applications.